

UNIT K UPPER LEVEL PLAN SCALE: 3/16" = 1'-0"

## **FLOOR PLAN GENERAL NOTES**

- ALL DIMENSIONS ARE TO FACE OF CURB, FACE OF CONCRETE OR MASO FACE OF FRAMING, OR CENTERLINE OF ORID UNLESS NOTED OTHERWISE. FINISH FLOOR ELEVATIONS ARE TO TOP OF CONCRETE, UNLESS NOTED OTHERWISE.
- OPERAL CONTRACTOR SHALL MANTAN THE JOB SITE IN A CLEAN AND ORDERLY CONDITION, PIECE OF GERSS AND LITTRE, UNDO, COMMERTION, ALL ALL AREAS TO BE REGOUNDED. MICH AND LEBRIS FROM THE PROMISES. ALL AREAS TO BE REGOUNDED.
  ALL CONDUST PEPING, IN ELECTRICAL ROOM TO BE CONCEALED WITHIN THE WALL CONSTRUCTION.
- WALL CONSTRUCTION. MICHARCAL, AND/OR PLANMED STARS, SUCH AS LIDERS, SHARE STARS, AND AND LIDERS, SHARE STARS, SHARE SHAR

- ALL EXITS SHALL HAVE EXIT SIGNS AND ALL BUIND CORRIDOR TURNS SHALL HAVE DIRECTIONAL EXIT SIGNS.
- 20. REFERENCE INTERIOR FINISH SCHEDULE FOR ALL INTERIOR FINISHES.
- BEINES SHALL BE PROVIDED WITH HATURAL VEHITATION BY MEANS OF DEPUBLIED EXTERNO PROMISS WITH AM AREA NOT LESS THAN 1/20 OF THE TOTAL ROOK MEED OF SHALL BE PROVIDED WITH A MICHANICALLY OPERATED WATHLATION STSTEM WITH A MICHANICALLY OPERATED WATHLATION STSTEM OF COURSE OF SHALL SHALL BE PROVIDED WITH A RESISTED EXCELS 10 FEET FROM SCOON, THE RESISTED SHALL BE PLACED MORE THAN 8 FEET ABOVE THE SCOON, THE RESISTED SHALL BE PLACED MORE THAN 8 FEET ABOVE THE FOCK OF DESCRIPT SHALL BE PLACED MORE THAN 8 FEET ABOVE THE FOCK OF DESCRIPT SHALL BE PLACED MORE THAN 8 FEET ABOVE THE FOCK OF DESCRIPT SHALL BE PLACED MORE THAN 8 FEET ABOVE THE


## **LEGEND**

EXTERIOR PLASTER WALL OVER METAL STUD (- A8.2)

EXISTING COLUMNS, SEE STRUCTURAL DWGS.

## FLOOR PLAN NOTES

- 1 STRUCTURAL COLUMN, SEE STRUCTURAL DRAWINGS.
- 2 4-0" x 3'-0" WINDOW WITH 1" THICK GLAZING, INSTALL AT 42" AFF. 3 MEZZANINE LINE ABOVE.
- 4 METAL CANOPY ABOVE. 5 ROOF ACCESS LADOER.
- EXISTING INSULATED WALL, IN-FILL GYPSUM BOARD IN OPEN AREA TO UNDERSIDE OF STRUCTURE.
- 7 ELECTRICAL SWITCHGEAR/EQUIPMENT, SEE ELECTRICAL DRAWINGS.



UNIT K LOWER LEVEL PLAN SCALE: 3/16" = 1'-0'

WARE MALCOMB

CENTER

VALENCIA BUSINESS 1382 VALENCIA TUSTIN, CALIFORNIA

 $\geq$ 

8

A2.1K

ALL INTERIOR PARTITIONS SHALL BE TAPED AND SANDED SMOOTH TO RECEIVE PAINT OR WALL FINISH MATERIAL. USE WATER RESISTANT GYPSUM BOARD AT ALL AREAS SUBJECT TO MOISTURE OR WHERE TILE IS USED.

PREPARE ALL FLOOR SURFACES AND WALLS AS REQUIRED TO RECEIVE FINISHES.

EXISTING CONCRETE WALL TO REMAIN



